

VX-520U

UHF Portable Radios



Rugged, Durable Portables with Unmatched Operating

- LIGHT WEIGHT AND COMPACT SIZE
- 16 CHANNEL CAPACITY
- 5 WATTS POWER OUTPUT
(Selectable to 1 Watt)
- 8-CHARACTER ALPHANUMERIC DISPLAY
- MIL-STD 810 C/D/E
- RUGGED CONSTRUCTION
- LOUD, CLEAR AUDIO OUTPUT
- 12.5/25 kHz BANDWIDTH
PROGRAMMABLE BY CHANNEL
- 3 PROGRAMMABLE FRONT-PANEL
FUNCTION KEYS
- CTCSS/DCS ENCODE + DECODE
- DTMF ANI DECODE
- DUAL 2-TONE DECODE
- MULTI-MODE SCAN
(incl. Dual Watch, Priority, Follow-Me)
- ARTS™ (Auto-Range Transponder System)
- BCLO, BTLO, AND TOT FUNCTIONS
- TX/RX BATTERY SAVER CIRCUIT
- PC PROGRAMMING
- RADIO-TO-RADIO CLONING



* Simulated LCD display

UHF Portable Radio

VX-520

32 Channels 5 W



Specifications

General Specifications	VX-520U
Number of Channels	32 Channels
Frequency Range	450-488 MHz (D)
Channel Spacing	12.5/25 kHz
Power Supply Voltage	7.2 VDC
Current Consumption	
Standby (Saver On)	19 mA
Standby (Saver Off)	50 mA
Receive	200 mA
Transmit	2.0/1.0 A
Battery Life	11 hrs. (13.3 hrs. w/saver)
Ambient Temperature Range	-30° C to +60° C (-22° F to +140° F)
Frequency Stability	±2.5 ppm
Dimensions	2.3"(W) × 5.9"(H) × 1.5"(D) (59 × 149 × 39 mm)w/FNB-29A 2.3"(W) × 6.7"(H) × 1.5"(D) (59 × 171 × 39 mm)w/FNB-29AL
Weight	1.21 lbs (547 g) w/o ANT w/FNB-29A 1.24 lbs (564 g) w/o ANT w/FNB-29AL

Receiver Specifications	Measurements made per EIA standard TIA/EIA-603
Circuit Type	Double-conversion Super-heterodyne
Sensitivity	
EIA 12 dB SINAD	0.25 µV
20 dB Quieting	0.35 µV
Adjacent Channel Selectivity	
25 kHz / 12.5 kHz channel spacing	75 dB / 65 dB
Intermodulation	72 dB
Spurious and Image Rejection	75 dB
Conducted Spurious Emissions	-57 dBm
Hum & Noise	40 dB / 45 dB
Audio Output	0.5 W @ 16 Ohms, 5 % THD

Transmitter Specifications	Measurements made per EIA standard TIA/EIA-603
Power Output	5.0 / 1.0 W
Modulation	16K0F3E , 11K0F3E
Conducted Spurious Emissions	60 dB Below Carrier
FM Hum & Noise	45 dB / 50 dB
Audio Distortion (@1 kHz)	<2.5 %

Military Standards 810 C/D/E	
MIL-STD 810C, Method 501.1, Procedure 1, High Temperature (storage)	MIL-STD 810D/E, Method 502.2/3, Procedure 1, Low Temperature (storage)
MIL-STD 810C, Method 501.1, Procedure 2, High Temperature (operational)	MIL-STD 810D/E, Method 502.2/3, Procedure 2, Low Temperature (operational)
MIL-STD 810C, Method 502.1, Procedure 1, Low Temperature	
MIL-STD 810C, Method 503.1, Procedure 1, Temperature Shock	MIL-STD 810D/E, Method 503.2/3, Procedure 1, Temperature Shock
MIL-STD 810C, Method 505.1, Procedure 1, Solar Radiation (Steady)	MIL-STD 810D/E, Method 505.2/3, Procedure 1, Solar Radiation (cycling)
MIL-STD 810C, Method 507.1, Procedure 2, Humidity	MIL-STD 810D/E, Method 506.2/3, Procedure 1, Rain (Blowing)
MIL-STD 810C, Method 514.2, Procedure 8, Vibration	MIL-STD 810D/E, Method 506.2/3, Procedure 2, Rain (drip)
MIL-STD 810C, Method 514.2, Procedure 10, Vibration	MIL-STD 810D/E, Method 507.2/3, Procedure 2, Humidity (induced)
MIL-STD 810C, Method 516.2, Procedure 1, Shock (basic design)	MIL-STD 810D/E, Method 509.2/3, Procedure 1, Salt Fog
MIL-STD 810C, Method 516.2, Procedure 5, Shock (bench handling)	MIL-STD 810D/E, Method 510.2/3, Procedure 1, Dust (blowing dust)
MIL-STD 810D/E, Method 500.2/3, Procedure 1, Low Pressure (storage)	MIL-STD 810D/E, Method 514.3/4, Procedure 1, Category 10, Vibration (minimum integrity)
MIL-STD 810D/E, Method 500.2/3, Procedure 2, Low Pressure (Operational)	
MIL-STD 810D/E, Method 501.2/3, Procedure 1, High Temperature (storage)	MIL-STD 810D/E, Method 516.3/4, Procedure 1, Shock (functional shock)
MIL-STD 810D/E, Method 501.2/3, Procedure 1, High Temperature (operational)	MIL-STD 810D/E, Method 516.3/4, Procedure 4, Shock (transit drop)
	MIL-STD 810D/E, Method 500.2/3, Procedure 6, Shock (bench handling)

Intrinsically Safe Approvals

The VX-520 UHF model has been given an intrinsically safe rating for use in ANSI/UL-913-88 Class I, II, and III. Division 1, Groups A, B, C, D, E, F, and G hazardous environments on models equipped with the Intrinsically Safe option.

The Vertex Standard Warranty*

Vertex Standard equipment includes an industry-leading 3-Year Limited Warranty on all transceivers and 1-Year Limited Warranty on all accessory items.

*U.S. and Canada

Accessories & Options

CLIP-4	Belt Clip
CN-1A	Antenna Jack Test Connector (Stud to BNC)
CS-500B	Overnight Desktop Charger (120 V)
CS-500C	Overnight Desktop Charger (240 V)
FBA-19	6 AA size Battery Case
FNB-29A	7.2 V 1700 mAh Ni-Cd Battery Pack (2.5 x 2.3 x 1.5 inch/63 x 59 x 39 mm)
FNB-29AIS	7.2 V 1700 mAh Ni-Cd Battery Pack Intrinsically Safe Battery (2.5 x 2.3 x 1.5 inch/63 x 59 x 39 mm)
FNB-29AL	7.2 V 1700 mAh Ni-Cd Battery Pack (3.3 x 2.3 x 1.5 inch/85 x 59 x 39 mm)
FNB-29ALIS	7.2 V 1700 mAh Ni-Cd Battery Pack Intrinsically Safe Battery (3.3 x 2.3 x 1.5 inch/85 x 59 x 39 mm)
FTT-7D	DTMF Keypad w/Decode Function
FVP-22	Voice Inversion Encryption
LCC-500	Leather Case (for VX-520 with FNB-29A)
LCC-520	Leather Case (for VX-520 with FNB-29AL)
LCS-2	Belt Swivel Attachment for LCC-500
MH-45E2B	Speaker Microphone
SBC-1	Swivel Belt Adapter (requires LCS-2)
VAC-520B	Rapid Desktop Charger (120 V)
VAC-520C	Rapid Desktop Charger (240 V)
VAC-6520	Rapid 6-unit Multi charger
VCM-1	Mobile Mounting Bracket for VAC-520
VPL-1D	Radio to Computer Programming Cable w/Software
VTP-20	VX-Trunk II Trunking Portable Logic Board



Vertex Standard US Headquarters

10900 Walker Street, Cypress, CA 90630, U.S.A.
Phone 714/827-7600; Fax 714/827-8100
<http://www.vxstdusa.com>